



(43) International Publication Date
4 August 2005 (04.08.2005)


PCT

(10) International Publication Number
WO 2005/070743 A1

- (51) International Patent Classification?: **B61K 9/10**,
G01N 29/10
- (21) International Application Number:
PCT/DK2005/000050
- (22) International Filing Date: 25 January 2005 (25.01.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PA 2004 00100 26 January 2004 (26.01.2004) DK
- (71) Applicants (for all designated States except US): **FORCE TECHNOLOGY** [DK/DK]; Park Allé 345, DK-2605 Brøndby (DK). **BANESTYRELSEN** [DK/DK]; Amerika Plads 15, DK-2100 Copenhagen Ø (DK).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **NIELSEN, Steen Arnfred** [DK/DK]; Tellusvej 23, DK-4040 Jyllinge (DK).
- BARDENSHTEIN, Alexander** [DK/DK]; Flintevænget 49, DK-2640 Hedehusene (DK). **LAURSEN, Niels Kjøppenborg** [DK/DK]; Møllehusene 2, 2. tv., DK-4000 Roskilde (DK).
- (74) Agent: **ZACCO DENMARK A/S**; Hans Bekkevolds Allé 7, DK-2900 Hellerup (DK).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: DETECTING RAIL DEFECTS



(57) **Abstract:** A method of detecting defects in a railway track rail, the rail (101) having a longitudinal centre plane and a surface, the surface including a running surface (102), the method comprising directing an excitation laser beam (106) to an excitation position (103) on the surface of the rail (101) to induce an ultrasonic wave in the rail (101); and directing a detection laser beam (108) to a detection position (104) on the surface of the rail (101) to detect at least one predetermined property of the induced ultrasonic wave; wherein the excitation position (103) and the detection position (104) are located on the running surface (102) and displaced from the longitudinal centre plane of the rail (101).

WO 2005/070743 A1



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments*

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*